

CTM

California Tomato Machinery



CTM COMMANDER 3240 TOMATO HARVESTER

High Capacity

The CTM Commander, designed for operation at 70 tons per hour (depending on field and crop conditions), lowers harvesting costs by providing more production from each machine.

Greater Recovery

The Commander's patented recovery reel and 2-stage shaker system are unequaled at tomato recovery. There is simply no better combination to minimize harvest losses. Shaker frequency is easily controlled for optimal performance for any variety and in all conditions.

Clean Harvest

Two-way dirt belts, outfitted with 32 channel dirt sorters, are standard equipment. High efficiency, 30" direct driven suction fans remove loose vines and trash through 14" diameter tubes, providing the maximum CFM airflow in the industry.

Operator Visibility & Controls

The operator platform is designed to provide the driver with clear visibility of the harvesting operation. Header controls are mounted on the steering column. Bulk loader, speed control, and other functions are located within easy reach to the right of the driver.

Maneuverability

The 225 hp 6081HF Tier II John Deere engine, in conjunction with 4-wheel hydrostatic drive and 4-wheel steering results in an easy-to-manuever, reliable machine with plenty of power to spare.

Long Life

Using the highest quality materials and a professional level of manufacturing ensures the harvester will produce for you now and into the future.

CTM COMMANDER 3240 TOMATO HARVESTER



STANDARD FEATURES

- ◆ 4-Wheel steering
- ◆ Automatic machine leveling
- ◆ Endless aftersort belts, 38" width
- ◆ Two-way dirt system conveyor, 32 channel
- ◆ Patented recovery reel for superior vine agitation
- ◆ Patented 2-stage shaker unequaled at tomato recovery
- ◆ Tread widths of 60, 63, or 66 available
- ◆ John Deere 6081HF Tier II diesel engine
- ◆ Limited slip traction control system
- ◆ 30" Rotor suction fans for superior performance
- ◆ 40 Channel colorsort
- ◆ 32" wide rear cross reservoir for non-stop trailer transitions
- ◆ One-man swing away elevator
- ◆ 13.00 x 24 radial tires
- ◆ Fold-up catwalks for easy transport
- ◆ 3-Speed ground drive system for increased road ability
- ◆ Heavy duty ground drive motors for unsurpassed reliability and torque
- ◆ Long-life urethane coated shaker tines
- ◆ Remote grease banks

OPTIONAL FEATURES

- ◆ Sickle, Rod Weeded, Disc Pickup
- ◆ 2-Weight or 3-Weight Head
- ◆ Vine Shredder
- ◆ Dual Color Sort System

DIMENSIONS

- A.** Length 36' 4" (11.07m)
- AA.** Transport Length 41' 2" (12.55m)
- B.** Wheel Base 12' 0" (3.66m)
- C.** Bulk Loader Dump Height
Standard 12' 4" (3.76m)
Extended 13' 0" (3.96m)
- D.** Bulk Loader Dump Width
Standard 5' 6" (1.68m)
Extended 7' 0" (2.13m)
- E.** Elevator Leg 10' 6" (3.20m)
- F.** Span from Wheel
Standard 18' 7" (5.66m)
Extended 20' 1" (6.12m)
- G.** Header Width 4' 7" (1.40m)
- H.** Width
Catwalks extended 16' 8" (5.08m)
- I.** Wheel – Gauge
Standard 5' 0" (1.52m)
Extended 5' 6" (1.68m)
- J.** Width
Catwalks retracted 14' 2" (4.32m)
- K.** Heights to Sunshade 10' 1" (3.07m)
- L.** Overall Height 10' 11" (3.33m)



California Tomato Machinery, LLC

2500 Industrial Avenue
Madera, CA 93637
Phone: 559-577-1800
Fax: 559-577-1899

Westside Equipment

18 Fink Road
Crows Landing, CA 95313
Phone: 209-856-4700
Fax: 209-837-4796

Westside Equipment

1230 Churchill Downs
Woodland, CA 95776
Phone: 530-298-5035
Fax: 530-666-3100

Westside Equipment

20289 W. Oakland
Five Points, CA 93624
Phone: 559-884-7700
Fax: 559-884-7701

www.tomatoharvester.com

